

BLACKTRACTION

RENEW_PROTECT_STRENGTHEN

RS

TECHNICAL DATA SHEET

Renewal, maintenance, cleaning and protection with long duration of effect WITHOUT SILICON, to porous plastic and many materials (PVC, protective films, paints with and without protection or by chemical reaction, carbon fiber), with hydro repellent protective finish, resistant to aggressive detergents and solvents, dry to the touch and paintable after absorption. Highly degreasing to clean and protect without damaging the plastic from abrasive pastes and waxes to: plastics, leather, PVC, rubber, metals (aluminum, copper and anodized plastic); paints from the resins without damaging the protective layer.

FEATURES:

Mix WITHOUT WAX AND SILICON which renews, enrich, maintains and protects the plastic construction (also anodized), PVC, metals and alloys, porous protective films laminated with multiple functions and characteristics:

- dry to touch finish, water repellent, resistant to aggressive detergents and solvents, heat-resistant and paintable after absorption;
- renews the surface of the porous polymer plastic respecting the original color tones;
- renews the maximum possible the shine and the intensity of the original color of the paint without protection or by chemical reaction;
- does not create visible thickness and follows the strain in the material without detaching as a paint;
- protects against deterioration old and new artifacts made with virgin or recycled plastic;
- protecting plastic and alloys from aggression of weathering and aggressive cleaner degradation;
- stabilizes long fine dust generated by the degradation of the plastic, and prevents the dispersion of pollutant dusts;
- renews and protects from degradation the carbon fiber parts and the gloss of the resins, respecting the transparency which characterizes the aesthetic appearance;
- clean the plastic from silicone, abrasive paste stains and wax (high degreasing properties);
- clean the paint to the strongly staining agents tree resin, without damaging the protective layer;
- clean and protects renews: PVC, aluminum, porous protective films;
- the application it' s easy with brush (with minimal waste compared to aerosol products where 25% of the product is dispersed) and is terminated with the passage of a cotton cloth to standardize the finish, or porous paper in order to obtain a glossy finish;
- IT' S NOT A PAINT; It does not come off, and when effect decays, allows to renew treatment;
- Kept closed, does not expire.

BLACKTRACTION

RENEW_PROTECT_STRENGTHEN

PROPERTY:

- WEATHER RESISTANCE: EXCELLENT
- RESISTANCE TO AGGRESSIVE CLEANERS: EXCELLENT
- UV RESISTANCE: EXCELLENT
- FLEXIBILITY: EXCELLENT
- COLOUR: YELLOW TRANSPARENT

SPECIFICATIONS

ABSORPTION at ambient temperature 20 °, dry to the touch after about 10 hours (time varying consequently the quality of the construction materials, to the degree of porosity of the material used and the method of application). Wait until the materials have completed absorption (dry to the touch) before proceeding to cleaning with strong detergents.

STORAGE

The product should be stored tightly closed in original container, away from direct or indirect heat, sunlight, and reach of children.

APPLICATION SYSTEMS

The product is ready for use. Do not dilute. Apply by brush or spray on dry surfaces and not overheated by sun exposure, to exceed 5 ° C. After application, wipe with a cloth treated surfaces, to ensure uniform finish. To get glossy finish, apply with rough paper for the workshop directly soaked in the product (not necessary wiped with a cloth).

YIELD

18/24 m² / liter (variable as a result of the material characteristics of porosity and state of degradation).

APPLICATION TEMPERATURE

+ 5 ° C + 40 ° C

- Apply with a brush or cotton cloth, uniformly on the surface;
- After a few minutes wipe with a soft cloth to achieve uniform finish;
- With a sponge, making sure to wet out, and then uniform with cloth;
- In spray to renew quickly large surfaces painted with colors without protection;
- With brush and then move on with microfiber cloth, to clean skin stained (not painted with water-based colors).

THE PRODUCT DON' T EXPIRE WELL CLOSED. NOT CORROSIVE. WITHOUT SILICON.

ALTERNATIVE: The application on plastic, performed using rough paper for the workshop directly soaked in the product, allows glossy finish of the black plastics and paints. This type of application needs more time for complete absorption. DON' T APPLY TO WET MATERIALS, OR HEATED BY EXPOSURE TO SUNLIGHT.

RENEW_PROTECT_STRENGTHEN

Hydrocarbon mixture / solutes, for the renewal and the black plastic protection to non-food use, with a yield equal to 55 ml / m² (hence the variable porosity characteristics, quality of raw material and state of decay).

NOT CORROSIVE; DON'T CONTAIN SILICONES; PRODUCT WITHOUT EXPIRY KEPT CLOSED.

To get the best possible result, you must follow the signs for surface preparation and compliance with the optimal conditions of use. The technical information are approximate. It is advisable to fit the specific conditions of use. The specification data and technical information have been calculated at + 15/30 ° C; in different conditions the data and the times suffer slight variations. Our recommendations on the use of the product are based on accurate observations and research carried out on their own. Were also taken into account the experience gained in the practical application. However, due to the enormous variety of materials and application conditions, you can get slightly different results.